


TITAN LITE SHIELDS



The name means what it says: LITE, and Kundel Titan means durable. Titan trench shields go to work for you.

How Kundel's trench shields compare to others

Common features

- P.E. Certified
- O.S.H.A. Compliant
- Tabulated Data
- 3/8" x 3" Cutting Bar

Kundel goes beyond...

- Formed Steel Design
- Continuous Steel Members
- 18" High Tapered Knife Edge
- Internal Pounding Members
- Reinforced Knife Edge
- Internal Stacking System
- Easy Slide Outside Edge
- One "C" Soil Depth Rating
- Vertical Reinforced Pounding Area
- Reinforced Through Wall Sockets

Your Local Trench Protection Specialist:

IMPORTANT: Kundel believes that every Contractor has individual concerns that must be addressed individually, not generically. Kundel uses years of in-the-trench experience, as well as in-depth knowledge of O.S.H.A. regulations, to custom fit you with a shoring or shielding system that will increase your production and profits, while working within O.S.H.A. guidelines, please call...

Titan 5 Lite

5" Side Walls
Production Depths 8' to 16'

Featuring:

- 18" Knife Edge Taper
- 5" (X) Strong Pipe Sockets
- 3/4" Thick Pounding Pads
- 2 1/2" Solid Stacking Lug Bar
- 3/8" x 3" Cutting Bar

Length	4'		5'		6'		8'		10'					
	Shield Wt.	Mach Wt.	Shield Wt.	Mach Wt.	Shield Wt.	Mach Wt.	Shield Wt.	Mach Wt.	Shield Wt.	Mach Wt.				
16' - ST	3131	21K	16' - K	3486	23K	16' - K	3942	26K	16' - K	4961	33K	16' - K	5980	40K
18' - ST	3580	24K	18' - K	3856	26K	18' - K	4590	31K	18' - K	5690	38K	18' - K	6965	46K
20' - ST	3891	26K	20' - K	4182	28K	20' - K	5395	35K	20' - K	6197	41K	20' - K	7592	51K
22' - ST	4208	28K	22' - K	4516	30K	22' - K	5795	36K	22' - K	6687	45K	22' - K	8188	55K
24' - ST	4662	31K	24' - K	4990	33K	24' - K	5997	40K	24' - K	7358	49K	24' - K	8989	60K
26' - ST	4963	33K	26' - K	5342	36K	26' - K	6393	43K	26' - K	8072	54K	26' - K	9569	64K

Titan 6 Lite

6 1/4" Side Walls
Production Depth 12' to 20'

Featuring:

- 18" Knife Edge Taper
- 5" (X) Strong Pipe Sockets
- 1 1/4" Thick Pounding Pads
- 2 1/2" Solid Stacking Lug Bar
- 3/8" x 3" Cutting Bar

Length	4'		5'		6'		8'		10'					
	Shield Wt.	Mach Wt.	Shield Wt.	Mach Wt.	Shield Wt.	Mach Wt.	Shield Wt.	Mach Wt.	Shield Wt.	Mach Wt.				
16' - ST	3723	26K	16' - K	4083	27K	16' - K	5296	36K	16' - K	6396	43K	16' - K	7791	53K
18' - ST	4230	28K	18' - K	4590	31K	18' - K	5803	38K	18' - K	6903	46K	18' - K	8298	55K
20' - ST	4737	31K	20' - K	5097	34K	20' - K	6310	43K	20' - K	7410	51K	20' - K	8805	57K
22' - ST	4900	33K	22' - K	5260	36K	22' - K	6539	45K	22' - K	7900	53K	22' - K	8910	58K
24' - ST	5300	36K	24' - K	5660	36K	24' - K	6939	46K	24' - K	8300	55K	24' - K	9800	60K
26' - ST	5700	36K	26' - K	6060	40K	26' - K	7339	51K	26' - K	8700	60K	26' - K	10,200	64K

Titan 8 Lite

8" Side Walls
Production Depth 16' to 30'

Featuring:

- 18" Knife Edge Taper
- 7" (X) Strong Pipe Sockets
- 1 1/2" Thick Pounding Pads
- 3" Solid Stacking Lug Bar
- 3/8" x 3" Cutting Bar

Length	4'		5'		6'		8'		10'	
	Shield Wt.	Mach Wt.	Shield Wt.	Mach Wt.	Shield Wt.	Mach Wt.	Shield Wt.	Mach Wt.	Shield Wt.	Mach Wt.
Call factory for availability 1.877.KUNDEL3										

LARGER 28'+ AND CUSTOM SHIELDS ARE AVAILABLE (Spreaders sold separately)